



NEROLAC

Colours that Care

NEROLAC IMPRESSIONS GLITTER FINISH



Excellent Metallic
Glitter



Versatile Product –
Use on Wall, Wood & Metal

PRODUCT DESCRIPTION

Nerolac Impressions Glitter Finish is a Water Based Metallic Lustrous Finish with Glitter For Interior/Exterior Walls, Wooden & Metal Surfaces. It is a Non-designer Finish and is an Ideal Product to Highlight the Surface with a Uniform Metallic Effect. It has Excellent Washability, Exterior Durability and Stain, Dust, Algae and Fungi Resistance.

FEATURES & BENEFITS



Excellent Metallic
Glitter



Good Exterior Durability



Versatile Product –
Use on Wall, Wood & Metal



Good Opacity &
Covering



Excellent Washability



Low VOC



Resistance to Dust pick up,
Algae & Fungi



Tintable with Nerolac
Machine Colourants

SURFACE PREPARATION

1.

Surface for treatment must be thoroughly cleaned of all laitance, loose material, oil, grease, etc.

2.

Mechanical means such as wire brushing can be used.

3.

All surface cracks upto 5 mm width should be properly treated with Nerolac Waterproof X crack filler. Cracks more than 5 mm and all separation gaps should be filled up with polymer modified mortar.

APPLICATION

A. Interior Surfaces –

Follow surface preparation method used for Nerolac Interior Emulsions.

1. Apply 2 coats of Impressions HD or Nerolac Pearls Emulsion and allow it to dry over night.
2. Dilute 1 L Nerolac Impression Glitter Finish with maximum 300-400 ml of clean water. Apply 2 to 3 coats with an interval of 4-6 h by brush or roller depending on ambient conditions.

B. Wood & Metal Surfaces –

1. Wooden surfaces should be primed with wood primer and Metal surfaces should be primed with Suitable Red Oxide / Yellow Metal Primer.
2. Dilute 1 L Nerolac Impression Glitter Finish with maximum 300-400 ml of clean water. Apply 2 to 3 coats with an interval of 4-6 h by brush or roller depending on ambient conditions.

C. Exterior Surfaces –

1. Follow surface preparation method used for Nerolac Exterior Emulsions.
2. Apply 2 coats of Nerolac Excel Exterior Emulsion OR Nerolac Excel Total Exterior Emulsion to get desired metallic effect Emulsions.
3. Thin 1 L Nerolac Impression Glitter Finish with maximum 300-400 ml of clean water. Apply 2 to 3 coats with an interval of 4-6 h by brush or roller.



*** Actual coverage may vary from the quoted coverage due to factors such as the application conditions, surface preparation and porosity.

PRECAUTIONS

1. Refer MSDS for "Nerolac Impressions Glitter Finish" for safety measures & precautions.
2. Store in well ambient conditions, Ventilated locations & away from the source of ignition and fire.
3. Keep away from children.
4. In case of eye/skin contact, wash with plenty of water.
5. Inhalation/Injection will cause danger. In case move to fresh air & consult medical practitioners in both the cases.
6. Do not apply when ambient temperature might drop to level below 10°C within 4 h of application.
7. New plaster should be allowed to cure for minimum 12 weeks.
8. Avoid extra thinning for better results.
9. Do not use universal stainers. Stir paint properly before application.
10. The container must be tightly closed when not in use.
11. Use personal protective equipments like rubber or polythene gloves, safety goggles/glasses & face mask.



SAFETY FEATURES

Non-Flammable



PACK SIZE

200 ml, 1 L



HEALTH & SAFETY PRECAUTIONS

- Avoid inhalation, eye and skin contact. In case of contact, wash with water and seek medical attention
- Do not pour the leftovers in the drain. Dispose off after natural drying



SHELF LIFE & STORAGE

- Shelf life is 24 months from the date of manufacturing in unopened condition
- Store in a cool & dry place
- Keep away from direct sunlight
- Thinned paint to be consumed within 24 h after thinning

DISCLAIMER

The product information and application details given by the company has been provided in good faith and is meant to serve only as a general guideline during usage. The performance claims made are based on the tests carried out under controlled conditions and our past experience with the type of products. Therefore actual performance will depend on local factors prevailing at that point of time. Users are advised to carry-out sample tests by taking trials to ensure the suitability of products for their requirement prior to full-scale usage of our products.

The Company is not liable for factors beyond its control such as application during adverse climatic conditions, use of improper application tools/techniques and surface preparation, any structural defects or the inferior quality of materials other than paints. The warranty/guarantee clauses shall accordingly be amended.