



## NEROLAC EXCEL TEXTURE FINISH - DHOLPUR

Nerolac Excel Dholpur finish is a high-build acrylic texture coating system for exterior surfaces. It provides an excellent finish for Exterior walls. It also provides excellent crack resistance & seepage resistance to the structures. This texture finish will suit all types of climatic conditions.

### PERFORMANCE FEATURES & BENEFITS



Durable and Long-Lasting Texture Finish



Weather Resistant



Excellent Adhesion



Water Resistant



Anti Algal



Easy Application

### AREAS OF APPLICATION



It is suitable for concrete, cement-based plasters, and lime-cement plasters.



Caution: Not recommended over lime wash.

### TECHNICAL DATA



**COVERAGE\***  
0.20 – 0.23 sq.mt/kg/coat



**RECOMMENDED DFT**  
Approximately 2 mm



**DRYING-TIME**  
Touch Dry (Hour) :1/2  
(@ 27+/-2 deg C & RH 60+/-5%)



**DRY TO RECOAT (HOUR)**  
16-18



**THINNING**  
Upto 5% water



**FLASH POINT**  
N / A



**SHELF LIFE #**  
6 Months

\*\*Actual coverage may vary depending on Material, condition of Application and workmanship.

# If stored appropriately under cover, above ground, away from direct heat and moisture and in well-sealed containers.

## METHOD OF APPLICATION

1. **Trowel application:** Apply the prepared mixture by evenly spreading it on the substrate using a stainless-steel trowel. Remove excess material to obtain aggregate size layer thickness and even surface with a short stainless-steel float. Even out the plaster to a uniform thickness by running a flat stainless float in a single direction—top to bottom / left to right. Up to 5 % water may be added at the time of painting, depending on application requirement.
2. For best results coat the surface with Nerolac Excel Anti Peel or Nerolac Excel Total All in one Exterior Acrylic Emulsion.
3. Clean spills and spatters immediately with soap and water. Clean hands and tools immediately after use with soap and warm water.

## SURFACE PREPARATION



The surface should be sound, clean, free of loose particles, dust, grease, chalk, fungus and mould.



Remove fungus growth with Nerolac Fungicidal wall wash treatment.



Clean surface by wire-brushing and wash with water.



Cracks in the substrate should be filled with Crack Fill Powder / Paste and the substrate is to be made uniform before application.

## PRECAUTIONS

1. Refer to the MSDS and Product Data sheet for usage.
2. Store in well ambient conditions and Ventilated locations.
3. Keep away from children.
4. In case of eye/skin contact wash with plenty of water.
5. Inhalation / Injection will cause danger. In case move to fresh air & consult medical practitioners in both the cases.
6. Do not apply when ambient temperature might drop to level below 10°C within 4 hrs of application.
7. New plaster should be allowed to cure for minimum 12 weeks.
8. Dilution above 5% will affect the performance.
9. The Bag must be tightly closed when not in use. Stir well before use.

## DISCLAIMER

The product information and application details given by the company has been provided in good faith and is meant to serve only as a general guideline during usage. The performance claims made are based on the tests carried out under controlled conditions and our past experience with the type of products, therefore actual performance will depend on local factors prevailing at that point of time. Users are advised to carry-out sample tests by taking trials to ensure the suitability of products for their requirement, prior to full-scale usage of our products. The Company is not liable for factors beyond its control such as application during adverse climatic conditions, use of improper application tools/techniques and surface preparation, any structural defects or the inferior quality of materials other than paints. The warranty/guarantee clauses shall accordingly be amended.