



NEROLAC EXTERIOR PRIMER SUPER

Nerolac Exterior Primer Super is a water based wall coating suitable for application on exteriors as a primer to exterior emulsions.

FEATURES & BENEFITS



Good Opacity and Whiteness



Does not require any water curing



Does not chalk and can be applied on freshly plastered surfaces



Improve the appearance of the emulsion topcoats

SURFACE PREPARATION

The surface to be painted must be free of all dust, grease, traces of paint flakes, algae, fungus, etc. The surface previously coated with paint must be cleaned thoroughly with a stiff coir brush, to remove dust, dirt chalking or any friable material. This ensures proper adhesion of the new paint system. In case of fungus affected area, apply a liberal coat of Nerolac Fungicidal Solution. Allow it to react for minimum 6-8 h. All structural cracks must be open in V-shape filled with White cement/cement based plasters, all leakage should be stopped, before actual painting. Freshly plastered surfaces must be allowed to cure completely. Apply top coats as follows.

RECOMMENDED USAGE

Nerolac Exterior Primer can be applied on a wide range of exterior cement plasters, exterior ceilings, asbestos sheet, concrete, etc. as a primer.

APPLICATION (FOR NEW MASONRY SURFACES)

Thin 1 Liter paint with 800 – 1000 ml of clean water.

Apply 1 coat by brush or roller and allow to dry for 3- 4 H.

PRECAUTIONS

1. Refer MSDS for "Nerolac Exterior Primer Super" for safety measures & precautions.
2. Store in well ambient conditions, Ventilated locations & away from the source of ignition and fire.
3. Keep away from children.
4. In case of eye/skin contact wash with plenty of water.
5. Inhalation / Injection will cause danger. In case move to fresh air & consult medical practitioners in both the cases.
6. Do not apply when ambient temperature might drop to level below 10°C within 4 h of application.
7. New plaster should be allowed to cure for minimum 12 weeks.
8. Avoid extra thinning for better results.
9. Do not use universal stainers. Stir well paint before application.
10. The container must be tightly closed when not in use.
11. Use personal protective equipments like rubber or polythene gloves, safety goggles / glasses & face mask.



***- Actual covering capacity may vary depending upon the method & condition of application, surface condition, temperature, wind velocity, application skills, surface roughness, surface porosity and shade

POST APPLICATION INSTRUCTIONS

Apply finishing coat within 7-8 days of primer application.

SHELF LIFE & STORAGE

- Shelf life is 24 months from the date of manufacturing in unopened condition.
- Store in a cool & dry place.
- Keep away from direct sunlight.
- Thinned paint to be consumed within 24 H after thinning.

HEALTH & SAFETY PRECAUTIONS

- Avoid inhalation, eye and skin contact. In case of contact, wash with water and seek medical attention.
- Do not pour the leftovers in the drain. Dispose off after natural drying.



SAFETY FEATURES
Non-Flammable



SHADE RANGE
White



PACK SIZE
1L, 4L, 10L & 20L

DISCLAIMER

The product information and application details given by the company has been provided in good faith and is meant to serve only as a general guideline during usage. The performance claims made are based on the tests carried out under controlled conditions and our past experience with the type of products. Therefore actual performance will depend on local factors prevailing at that point of time. Users are advised to carry-out sample tests by taking trials to ensure the suitability of products for their requirement prior to full-scale usage of our products.

The Company is not liable for factors beyond its control such as application during adverse climatic conditions, use of improper application tools/techniques and surface preparation, any structural defects or the inferior quality of materials other than paints. The warranty/guarantee clauses shall accordingly be amended.