



## NEROLAC IMPRESSIONS METALLIC DESIGNER FINISH

# NEROLAC PAINT+



### PRODUCT DESCRIPTION

Nerolac Impressions Metallic Designer finish is a premium-quality, Special effect designer series range that creates a variety of special effects and textures on interior walls and is based on pure acrylic emulsion.

### PERFORMANCE FEATURES & BENEFITS

	Can make Various Designs with Different Application Tools		Excellent Workability
	Very good AntiFungal Resistance		Smooth Metallic Finish with sheen
	Excellent Stain Resistance		Excellent Washability

### SURFACE PREPARATION

1. Rub the surface using a suitable abrasive paper & wipe it off to ensure that the surface is clean, dry & free from dirt, grease, wax or any other defective or poorly adhering material.
2. Treat fungus affected areas using Nerolac Fungicidal Solution & allow it to react for 6-8 h.
3. Apply a coat of suitable Primer\*\* (water/solvent thinnable) followed by Putty### to level and smoothen the surface.
4. Sand the surface with emery paper 180 & wipe clean. Apply another coat of suitable Primer\*\*. Sand the surface with emery paper 320 & wipe clean.
5. Apply Base (2-3 coats) Nerolac Impressions HD. Dry in 4-6 h in between the coats.

### RECOMMENDED USAGE

Nerolac Impressions Metallic Designer finish can be applied on the interior surfaces, on new & previously painted surfaces such as plaster, brickwork, cement rendering, concrete, hardboard, building boards, etc.

### RECOMMENDED SYSTEM FOR APPLICATION

For New Masonry Surfaces

1. Primer\*\* (1 coat), Dry# in 4-6 h.
2. Putty###, Dry in 6-8 h.
3. Primer\*\* (1 coat), Dry# in 4-6 h.
4. Base (2-3 coats) Nerolac Impressions HD, Dry in 4-6 h in between the coats.
5. Finish Coat (1 Coat) Nerolac Impressions Metallic Finish Wall Emulsion

For Repainting on Smooth Lime/Distemper/Emulsion/Enamel Masonry Surfaces skip steps 1 & 2 and start with step 3.

Sand the surface with Emery paper and wipe clean before application of subsequent coat.

\*\*Nerolac Premium Primer (Water Thinnable / Solvent Thinnable) or Nerolac Popular Primer (Water Thinnable / Solvent Thinnable).

###Nerolac Wall Putty or Nerolac Cement Putty.

#Minimum 8 h for Solvent Thinnable Primer & minimum 4-6 h for Water Thinnable Primer.

### PRECAUTIONS

1. Refer MSDS for "Nerolac Impressions Metallic Designer finish" for safety measures & precautions.
2. Store in well ambient conditions, ventilated locations & away from sources of ignition and fire.
3. Keep away from children.
4. In case of eye / skin contact, wash with plenty of water.
5. Inhalation / Injection is dangerous. In either case, move to fresh air & consult a medical practitioner.
6. Do not apply when ambient temperature might drop to a level below 10°C within 4 h of application.
7. New plaster should be allowed to cure for minimum 12 weeks.
8. Avoid extra thinning for better results.
9. The container must be tightly closed when not in use. Stir well before use.
10. Use safety equipment like rubber or polythene gloves, safety goggles / glasses & face mask.

## TECHNICAL DATA



\*\*\*Actual coverage may vary depending on method, Condition of Application, Type of Tools, Surface Porosity & Shade. Use of felt Roller may reduce coverage upto 50%.

## POST APPLICATION INSTRUCTIONS

Surfaces painted with Nerolac Impressions Metallic Designer finish are wash-able by sponging with mild soap and water after a minimum of 2 weeks drying to remove ordinary stains and everyday dirt.



### SAFETY FEATURES

Non-Flammable



### PACK SIZE

1 L & 200 ml



### SHADE RANGE

As per Nerolac Impressions Metallic  
Finish Wall Emulsion Shade Card



### SHELF LIFE

2 years from the date of manufacturing, when  
stored in the original tightly closed containers,  
away from direct sunlight & excessive heat

## DISCLAIMER

The product information and application details given by the company has been provided in good faith and is meant to serve only as a general guideline during usage. The performance claims made are based on the tests carried out under controlled conditions and our past experience with the type of products. Therefore actual performance will depend on local factors prevailing at that point of time. Users are advised to carry-out sample tests by taking trials to ensure the suitability of products for their requirement prior to full-scale usage of our products.

The company is not liable for factors beyond its control such as application during adverse climatic conditions, use of improper application tools/techniques and surface preparation, any structural defects or the inferior quality of materials other than paints. The warranty/guarantee clauses shall accordingly be amended.