



NEROLAC BEAUTY LITTLE MASTER



PRODUCT DESCRIPTION

Nerolac Beauty Little Master is a specially developed economical product with a smooth finish with better whiteness, opacity and coverage compared to normal distemper. It is formulated by using ideal combination of pigments and extenders dispersed in a copolymer emulsion for smooth and pleasant matt finish.

PERFORMANCE FEATURES & BENEFITS

	Plastic Emulsion		Good Whiteness
	Smooth & Pleasing Matt Finish		Ease of Application
	Good Coverage		Economical Product with Optimum performance

SURFACE PREPARATION

1. Ensure the surface is clean, dry, free from all defective or poorly adhering materials by rubbing down, using suitable abrasive paper & thereafter wiped off.
2. Treat fungus affected areas using Nerolac Fungicidal Solution. Allow it to react for 6-8 h.
3. Apply a coat of suitable Primer** followed by Nerolac Wall Putty*** to level the dents and make the surface uniform. Sand the surface with emery paper 180 and wipe clean.
4. Again apply a coat of suitable primer**. Sand the surface with emery paper 320 and wipe clean.
5. Then apply two to three coats of Nerolac Beauty Little Master.

RECOMMENDED USAGE

Nerolac Beauty Little Master is recommended for interior wall surface such as ceilings, plasters, bricks, asbestos, etc.

RECOMMENDED SYSTEM FOR APPLICATION - For New Masonry Surfaces

1. Primer** (1 coat), Dry# in 4-6 h.
2. Putty***, Dry in 6-8 h.
3. Primer** (1 coat), Dry# in 4-6 h.
4. Finish Nerolac Beauty Little master (2-3 coats), Dry min. 4-6 h in between coats.

For Repainting on Smooth Lime/Distemper/Emulsion/Enamel Masonry Surfaces skip steps 1 & 2 and start with step 3.

Sand the surface with Emery paper and clean before application of subsequent coat.

**Nerolac Premium or Popular Primer (Water thinnable / Solvent thinnable).

***Nerolac Wall putty or Nerolac Cement putty.

#Minimum 8 h for solvent thinnable primer & minimum 4-6 h for water thinnable Primer.

PRECAUTIONS

1. Refer MSDS for "Nerolac Beauty Little Master" for safety measures & precautions.
2. Store in well ambient conditions, ventilated locations & away from sources of ignition and fire.
3. Keep away from children.
4. In case of eye / skin contact, wash with plenty of water.
5. Inhalation / Injection is dangerous. In either case, move to fresh air & consult a medical practitioner.
6. Do not apply when ambient temperature might drop to a level below 10°C within 4 h of application.
7. New plaster should be allowed to cure for minimum 12 weeks.
8. Avoid extra thinning for better results.
9. Can be tinted with Nerolac Hi-Power Universal Stainer before thinning. Do not add more than 5% of Nerolac Hi-Power Universal Stainer. Stir the tinted paint well, after tinting & before application.
10. The container must be tightly closed when not in use. Stir well before use.
11. Use safety equipment like rubber or polythene gloves, safety goggles / glasses & face mask.

TECHNICAL DATA



**Actual coverage may vary depending on method, Condition of Application, Type of Tools, Surface Porosity & Shade. Use of felt Roller may reduce coverage upto 50%.

POST APPLICATION INSTRUCTIONS

Surfaces painted with Nerolac Beauty Little Master Interior Emulsion are washable by sponging with mild soap and water. After a minimum of 2 weeks drying to remove ordinary stains and every day dirt.



SAFETY FEATURES

Non-Flammable



PACK SIZE

1 L, 4 L, 10 L & 20 L and
1 kg, 5 kg, 10 kg & 20 kg



SHELF LIFE

2 years from the date of manufacturing, when stored in the original tightly closed containers, away from direct sunlight and excessive heat



SHADE RANGE

As per Nerolac Colour Scapes
Fandeck & Shade Card

DISCLAIMER

The product information and application details given by the company has been provided in good faith and is meant to serve only as a general guideline during usage. The performance claims made are based on the tests carried out under controlled conditions and our past experience with the type of products. Therefore actual performance will depend on local factors prevailing at that point of time. Users are advised to carry-out sample tests by taking trials to ensure the suitability of products for their requirement prior to full-scale usage of our products.

The company is not liable for factors beyond its control such as application during adverse climatic conditions, use of improper application tools/techniques and surface preparation, any structural defects or the inferior quality of materials other than paints. The warranty/guarantee clauses shall accordingly be amended.