



**NEROLAC  
PAINT+**

# Arabesque

## DESCRIPTION

**Arabesque** is formulated with micro-particles to give the product magical light and dark contrast effects, a velvety feel and intriguing silky reflections.

## PRODUCT FEATURES

- Reflections: Gradations of delicate shades
- Velvety: Delicate and soft-touch effects
- Rapid laying: Very fast application
- Lead-free
- Low VOC
- Single Coat Application

## APPLICATION PROCEDURE

SYSTEM	PRODUCT	DILUTION	APPLICATION TOOLS	NUMBERS OF COATS	DRYING TIME
Primer	Nerolac Premium Primer WT	50% by volume with water	Brush, Roller or Spray	1 coat	4-5 hours
Putty	Nerolac Acrylic Wall Putty	No	Putty knife blade (Patra)	2 coats	4-5 hours
	OR				
	Nerolac Cement Putty	25-35% by weight with Water	Putty knife blade (Patra)	2 coats	4-5 hours
Primer/ Self-Priming	Nerolac Premium Primer WT	50% by volume with water	Brush + Roller, Spray, Felt roller	1 coat	4-5 hours
	OR				
	Kansai Select Texture Basecoat	50% by volume with water	Brush + Roller, Felt roller	1 coat	4-5 hours
Base Coat	Kansai Select Texture Basecoat	20-30% by volume with water	Brush + Roller, Felt roller	2 coats	4-5 hours
Designer Finish	Kansai Select Arabesque	The product does not need to be diluted; it is ready to use.	Brush	1 coat	4-5 hours

## ARABESQUE APPLICATION

- Apply Arabesque (chosen shade) with a brush in a crosshatch pattern to a surface of 1 to 1.5 m<sup>2</sup>, let it dry for a short while then go over with empty brush to orient the microparticles and create a light-dark effect.
- Finally, smoothing it out with a trowel to accentuate this light-dark effect. Continue decorating the entire wall in the same manner.
- It is advisable to make a small test before executing the work.
- We also recommend mixing any different batches of product after colouring and before application.
- Kansai Nerolac Paints strongly recommends the use of its own **Kansai Select Texture Basecoat**, considering it to be the most suitable basecoat for enhancing both the aesthetic aspect and the compatibility of the products in the various application coats.
- In case this does not happen, Kansai Nerolac Paints is not responsible for any unsuccessful work.

## TECHNICAL CHARACTERISTICS

PACKAGING	1 Ltr
COVERAGE	75-95 sq.ft/L/coat
SPECIFIC WEIGHT	1.09 - 1.135
STORAGE AND WORKING TEMPERATURE	Min. + 5°C, Max. + 40°C
SHADE RANGE	Kansai Select Arabesque
APPLICATION TOOLS	Brush & Trowel
COUNTRY ORIGIN	ITALY
SHELF LIFE	2 Years
V.O.C. CONTENT	<20 gm/ltr
LEAD CONTENT	Lead content does not exceed 90 parts per million