

DESCRIPTION

Positano is a water-based decoration, medium breathable, and ecological. It reproduces the beauty in a matt version of the most classic decorative products, overcoming the difficulty of application to draw deep nuances of movement on the wall. The meticulous selection of raw materials leads to a prestigious decorative effect, and at the same time, it is extremely easy to apply. Its hallmarked velvety chiaroscuro effect, delicate shades, and particular matte finish will make every decorated interior wall look attractive.

PRODUCT FEATURES

- **Rapid laying:** Fast and very simple application
- **Easy Laying:** Effect achieved by irregular application
- **Avoid errors:** Transform touch-ups into design with ease
- **Matt Finish**
- **Lead-free**
- **Low VOC**

APPLICATION PROCEDURE

SYSTEM	PRODUCT	DILUTION	APPLICATION TOOLS	NUMBERS OF COATS	DRYING TIME
Primer	Nerolac Premium Primer WT	50% by volume with water	Brush, Roller or Spray	1 coat	4-5 hours
Putty	Nerolac Acrylic Wall Putty	No	Putty knife blade (Patra)	2 coats	4-5 hours
	OR				
	Nerolac Cement Putty	25-35% by weight with Water	Putty knife blade (Patra)	2 coats	4-5 hours
Primer/ Self-Priming	Nerolac Premium Primer WT	50% by volume with water	Brush + Roller, Spray, Felt roller	1 coat	4-5 hours
	OR				
	Kansai Select Texture Basecoat	50% by volume with Water	Brush + Roller, Felt roller	1 coat	4-5 hours
Base Coat	Kansai Select Texture Basecoat	20-30% by volume with water	Brush + Roller, Felt roller	2 coats	4-5 hours
Top Coat	Kansai Select Positano	The product does not need to be diluted; it is ready to use.	Trowel	2 coats	4-5 hours

POSITANO APPLICATION

- Apply first coat of Positano (chosen shade) by a trowel in alternating strokes (not to be applied in one direction only).
- When the first coat is nicely dry, proceed with the second coat using the same application method as the first.
- Applying Positano with alternating strokes, randomly and not in a single direction (all horizontal or vertical), will bring out the precious translucent and matt effect of the final product when dry.
- It is advisable to make a small test before executing the work. We also recommend mixing any different batches of product after colouring and before application.
- Kansai Nerolac Paints strongly recommends the use of its own **Kansai Select Texture Basecoat**, considering it to be the most suitable basecoat for enhancing both the aesthetic aspect and the compatibility of the products in the various application coats.
- In case this does not happen, Kansai Nerolac Paints is not responsible for any unsuccessful work.

TECHNICAL CHARACTERISTICS

PACKAGING	1 Ltr
COVERAGE	70-90 sq.ft/L/coat
SPECIFIC WEIGHT	0.95 - 1.00 Kg/Ltr
STORAGE AND WORKING TEMPERATURE	Min. + 7°C, Max. + 35°C
SHADE RANGE	Kansai Select Positano Catalogue
APPLICATION TOOLS	Trowel
COUNTRY ORIGIN	ITALY
SHELF LIFE	2 Years
V.O.C. CONTENT	Less than 20 gm/Ltr
LEAD CONTENT	Lead content does not exceed 90 parts per million