



**NEROLAC
PAINT+**

Shikisai

DESCRIPTION

Inspired by the natural stones found in nature, Shikisai brings a Matt Stone finish with multi-coloured patterns to your walls. Shikisai seamlessly amalgamates elegance and luxury in a calm finish which amps up your space.

PRODUCT FEATURES

- Multicolour Finish
- Low VOC
- Excellent Antifungal resistant
- Easy to Apply
- Matt Stone Finish.

SURFACE PREPARATION:

- Ensure that the plastered surface is clean, dry & free from any loose or poorly adhering material, dirt, grease etc.
- Apply a coat of Nerolac Premium Primer Water based interior primer and allow it to dry.
- Apply the Nerolac Acrylic Wall putty to level-out the undulations. Sand the surface with emery paper no. 220 and wipe it clean.
- Apply another coat of primer and allow it to dry. Sand the surface with emery paper no. 320 and wipe it clean with a cloth before painting.
- Apply two coats of Nerolac Impression HD as base coat.

RECOMMENDATION OF USE:

Kansai Shikisai should be applied without dilution by Spray application. Spray gun to be use gravity feed with paint cup with 2.0 to 2.5 mm nozzle.

DRYING TIME	Surface dry 30 min
DILUTION	No Dilution
RECOATING	Minimum 3-4 hrs@ 27±2°C & RH 60±5%
SHEEN	Matt Sheen
VOC	<50 gms/Liter (IS 101)
FLASH POINT	NA
SHELF LIFE	2 years from date of MFG

***Actual coverage may vary depending on method, condition of application, Type of Tools, Surface porosity & shades.



POST APPLICATION INSTRUCTION:

For the best performance, ensure dry dust-cleaning at regular intervals. Allow a drying-time of 3 weeks for proper film-formation before doing any sponge cleaning with a mild soap-solution or mineral turpentine.

Safety Features: Non-Flammable

Pack Sizes: 1 ltr.

Shelf Life: 2 years from the date of manufacturing, when stored in the original tightly closed containers, away from direct sunlight and excessive heat.

PRECAUTIONS:

- Refer to the MSDS for "Kansai Select Shikisai "for safety measures & precautions.
 - Store in well-ambient conditions, ventilated locations & away from any source of ignition and fire.
 - Do not use mechanical mixer to prevent color particle collapsing.
 - Keep it away from children.
 - In case of eye/skin contact, wash with plenty of water.
 - Inhalation/Injection will cause danger. In either case, get fresh air & consult medical practitioners.
 - Do not apply when the ambient temperature might drop to levels below 10°C within 4 hours of application.
 - Ideal moisture % of the wall should be below 12% and pH between 7-11.
 - The new plaster should be allowed to cure for a minimum of 12 weeks.
 - Avoid thinning.
 - The container must be tightly closed when not in use. Stir well and strain before use.
 - Use safety equipment's like rubber or polythene gloves, safety goggles/glasses & face masks.
- 