



SELECT Tracce

DESCRIPTION

Tracce is a lime based product that creates a unique textured effect bringing a natural and rustic charm to your walls. It blends our finest decorative traditions with contemporary demands for immediacy and personalisation in interior design.

PRODUCT FEATURES

- **Breathable:** No mould or residual moisture in the wall
- **Professional:** Application for professionals
- **Natural Concrete Effect**
- **Lead-free**
- **Low VOC**
- **Single Coat Application**

APPLICATION PROCEDURE

| SYSTEM | PRODUCT | DILUTION | APPLICATION TOOLS | NUMBERS OF COATS | DRYING TIME |
|-------------------------|--------------------------------|--|------------------------------------|------------------|-------------|
| Primer | Nerolac Premium Primer WT | 50% by volume with water | Brush, Roller or Spray | 1 coat | 4-5 hours |
| Putty | Nerolac Acrylic Wall Putty | No | Putty knife blade (Patra) | 2 coats | 4-5 hours |
| | OR | | | | |
| | Nerolac Cement Putty | 25-35% by weight with Water | Putty knife blade (Patra) | 2 coats | 4-5 hours |
| Primer/ Self-Priming | Nerolac Premium Primer WT | 50% by volume with water | Brush + Roller, Spray, Felt roller | 1 coat | 4-5 hours |
| | OR | | | | |
| | Kansai Select Texture Basecoat | 50% by volume with water | Brush + Roller, Felt roller | 1 coat | 4-5 hours |
| Designer Finish | Kansai Select Tracce | The product does not need to be diluted; it is ready to use. | Trowel | 1 coat | 4-5 hours |

TRACCE APPLICATION

- Apply Tracce with a stainless-steel trowel, spreading the paint to obtain a uniform thickness of max. 2 mm.
- Make sure the paste forms a perfectly plane surface, since the product is applied in a single layer.
- It is advisable to make a small test before executing the work.
- We also recommend mixing any different batches of product after colouring and before application.
- Kansai Nerolac Paints strongly recommends the use of its own **Kansai Select Texture Basecoat**, considering it to be the most suitable basecoat for enhancing the aesthetic aspect as well as the compatibility of the products in the various application coats.
- In case this does not happen, Kansai Nerolac Paints is not responsible for any unsuccessful work.

TECHNICAL CHARACTERISTICS

| | |
|---------------------------------|---|
| PACKAGING | 1 Kg , 5 Kg |
| COVERAGE | 5-7 sq.ft/Kg/coat |
| SPECIFIC WEIGHT | 1.6 - 1.7 Kg/Ltr |
| STORAGE AND WORKING TEMPERATURE | Min. + 5°C, Max. + 40°C |
| SHADE RANGE | Kansai Select Tracce Catalogue |
| APPLICATION TOOLS | Trowel |
| COUNTRY ORIGIN | ITALY |
| SHELF LIFE | 1 Year |
| V.O.C. CONTENT | Less than 20 gm/Ltr |
| LEAD CONTENT | Lead content does not exceed 90 parts per million |